

Tubing Specification Chart

OD (in.)	Connection	Grade	Weight (lb/ft)	Connection OD (in.)		Connection ID (in.)	Tube ID (in.)	Tube Drift (in.)	New Tube	New Tube	New Tube
				Box	Pin				Burst (psi)	Collapse (psi)	Tensile (psi)
2.375	EUE (8RD)	N-80	4.7	3.063	3.063	1.995	1.995	1.901	11,200	11,776	104,338
2.375	PH-6	P-110	5.95	2.906	2.906	1.805	1.867	1.773	20,587	21,012	186,173
2.375	PH-6	AC-95	7.7	3.125	3.125	1.645	1.703	1.609	23,520	23,077	204,470
2.875	EUE (8RD)	N-80	6.5	3.668	3.668	2.441	2.441	2.347	10,567	11,165	144,962
2.875	EUE (8RD)	L-80	6.5	3.668	3.668	2.441	2.441	2.347	10,567	11,165	144,962
2.875	EUE (8RD)	P-110	6.5	3.668	3.668	2.441	2.441	2.347	14,530	14,547	199,323
2.875	PH-6	P-110	7.9	3.438	3.438	2.265	2.323	2.229	18,480	19,092	247,889
2.875	TSHD	L-80	8.7	3.5	3.5	2.2	2.259	2.165	14,998	15,305	198,708
2.875	TS-6	L-80	8.7	3.5	3.5	2.2	2.259	2.165	14,998	15,305	198,708
2.875	PH-6	P-110	8.7	3.5	3.5	2.2	2.259	2.165	20,623	21,044	273,224
3.500	EUE (8RD)	N-80	9.3	4.5	4.5	2.992	2.992	2.867	10,160	10,535	207,215
3.500	PH-6	L-80	12.95	4.313	4.313	2.687	2.75	2.625	15,000	15,306	294,524
3.500	BTS-6	L-80	12.95	4.313	4.313	2.687	2.75	2.625	15,000	15,306	294,524
3.500	PH-6	P-110	12.95	4.313	4.313	2.687	2.75	2.625	20,625	21,046	404,971
3.500	PH-6	AC-95	15.8	4.5	4.5	2.485	2.548	2.423	22,610	22,326	429,598
3.500	BTS-6	T-95	15.8	4.5	4.5	2.485	2.548	2.423	22,610	22,326	429,598
3.500	PH-6	T-95	15.8	4.5	4.5	2.485	2.548	2.423	22,610	22,326	429,598
3.500	TS-6	C-95SS	15.8	4.5	4.5	2.485	2.548	2.423	22,610	22,326	429,598
4.500	LTC 8RD	P-110	11.6	5	5	4	4	3.875	10,694	7,576	367,173
4.500	BTS-6	L-80	15.5	5.125	5.125	3.765	3.826	3.701	10,484	11,085	352,595
4.500	PH-6	AC-95	15.5	5.125	5.125	3.765	3.826	3.701	12,450	12,765	418,706
4.500	TS-6	C-95SS	15.5	5.125	5.125	3.765	3.826	3.701	12,450	12,765	418,706
4.500	PH-6	P-110	15.5	5.125	5.125	3.765	3.826	3.701	14,416	14,341	484,818
4.500	BTS-6	P-110	15.5	5.125	5.125	3.765	3.826	3.701	14,416	14,341	484,818
4.500	TS-6	P-110	15.5	5.125	5.125	3.765	3.826	3.701	14,416	14,341	484,818
4.500	TSHD	Q-125	17	5.25	5.25	3.665	3.74	3.615	18,474	19,328	614,809
4.500	PH-4	C-95	24	5.563	5.563	3.3	3.38	3.255	20,689	20,702	658,502
4.500	PH-4	NT-95SS	24	5.563	5.563	3.3	3.38	3.255	20,689	20,702	658,502
5.000	HYDRIL CS	AC-95	23.2	5.7	5.7	3.964	4.044	3.919	15,894	16,428	645,107

War Horse Fishing and Rental Tools, Inc.

www.warhorsecompanies.com • 888-927-2070